



ARCWHEEL



- Improved Torque Retention (ITR) technology
- Three-step painting process including a zinc phosphate bath, e-coat primer, and Acrylic-Enamel coating on outboard side
- Available in White, Silver, and Black Spoke/Mod

SIZE	OS	CB	LCC
13X4.5 5X4.5	0	3.19	1660
13X4.5 5X4.5	0	2.99	1660
14X6 5X4.5	0	3.19	1870
14X6 5X4.5	0	3.27	1870
15X5 5X4.5	0	3.19	1870
15X5 5X4.5	-0.12	3.31	1870
15X5 5X4.5	0	3.31	1870
15X5 5X4.75	-.055	3.31	1870
15X5 5X4.75	-.031	3.31	1870
15X5 5X5.0	0	3.19	1870
15X5 5X5.0	-0.12	3.31	1870
15X5 5X5.0	0	3.31	1870
15X5 5X5.5	0.67	4.25	1870
15X6 5X4.5	0	3.19	2830

SIZE	OS	CB	LCC
15X6 5X4.5	0	3.31	2830
15X6 4X4.75	0	3.31	2830
15X6 5X5.0	0	3.31	2830
15X6 5X5.5	0	4.25	2830
15X6 6X5.5	0	4.25	2830
16X6 6X5.5	0	4.25	3500
16X6 6X5.5	0.5	4.25	3500
16X6 8X6.5S	0	4.88	3750
16X6 8X6.5S	0.51	4.88	3750
16X6 8X6.5S	0	5.12	3750
16X6 8X6.5SHD	-0.51	4.88	4400
16X6 8X6.5SHD	0.51	4.88	4400
16X6 8X6.5SHD	0	4.88	4400
16X6 8X6.5SHD	0	5.12	4400